SOLARAI **EB2 GROUP**

Flexible 2-Motor BACnet MS/TP Controller



PRODUCT HIGHLIGHTS

- **▶** OUT-OF-THE-BOX FUNCTIONALITY **☆** ZERO-CONFIG SIMPLE-SWITCH™ DEFAULTS
- ☐ CONFIGURABLE WITH MOBILE APP (ADD-ON REQ'D)
 - SENSOR RESPONSE
 - **PRIORITIES**
 - **EXTERNAL INPUTS / CONTROLS INTEGRATION**
- BACNET MS/TP INDUSTRY-STANDARD NETWORK
- SCALABLE (STANDALONE TO WHOLE BUILDING)
- ▲ UPGRADEABLE FEATURES (IN-FIELD UPGRADES)

6 Contact Closure Inputs

 Universal: 110-240VAC 2 Motor Outputs

HARDWARE FEATURES

- Simple-Switch™ default bindings for onboard/network motors
- · Flexible Control Groups
- Network Mappable*
- Configurable Responses including Scene Control
- Pluggable Switch and Network Connectors for Easy Installation
- Optional programming through network or on-board MicroUSB

*requires optional network

WORKS WITH...

- Roller Shades
- Venetian Blinds
- Louvers
- Rack Arm Systems
- Skylights
- Operable Windows

NATIVE BACnet

BMS integration

And more...

device capable of independent or grouped control for up to two motorized systems. It is designed for response based automation and out-of-the-box low voltage control of roller shades, venetian blinds, operable louvers, and other devices using any standard 4-wire AC motor.

Embedia's Solarai™ EB2 GROUP is a BACnet MS/TP

An optional BACnet MS/TP communication network, often not required for smaller installations, adds flexibility through additional programming and interface options. By implementing the same unique distributed intelligence architecture pioneered by Embedia's premium PLUS level controls. The GROUP controller is both scalable and reliable. The 2 and 4-Motor versions of the GROUP can be upgraded in the field to PLUS level functionality.

Each controller has 3 pairs of contact closure inputs with fully programmable, priority based, response profiles. Each input can be reconfigured to control any group of motors on the entire network (where available). A simple dry contact switch, or any other device capable of closing a contact, can be used for advanced group and scene control.

provide By default, the onboard input pairs forward/reverse switch control for the attached motors as well as networked motors on Simple-Switch™ channels 1. 2. and MASTER:

Closing a contact momentarily will start the motors moving in the corresponding direction. Closing both contacts will stop the motors

Holding a contact closed for more than 1.5 seconds will move the motors in the corresponding direction until the contact is released.































· No gateway device required for



SOLARAI EB2 GROUP

SIMPLE-SWITCH™ **DEFAULTS**

SWITCH INPUT

M O		1	‡2	‡3	 \$4	 \$5
O R	⊚1	Ø	\bigcirc		N/A	N/A
СН	⊚2	S		S	N/A	N/A
E A N E	⊚3	S	S		N/A	N/A
N E	⊚4	S		S	N/A	N/A

COMPANION PRODUCTS

SW7 (Simple-Switch™, multiple options)

- **Push Button Switches**
- Contact Closure, USB, or RF Standard "Decorator" Styling
- **Custom Engraving Available**

USB Addons

- USBIF-AV serial integration USBIF-DCI12 dry contact inputs USBIF-RF-Z RF (mesh) receiver for wireless switches
- USBIF-WiFi WiFi network

- Sensor Inputs
- AV/BMS Integration BACnet MS/TP-IP Router (optional)

Control Panel Software

Graphical User Interface for Advanced system Management (network requried)

Third-Party Devices/Switches

- **Contact Closures**
- Dry Contact Outputs Off-the-Shelf Switches
- A/V / BMS Outputs

WARRANTY

All Embedia products carry a standard 2-year product replacement warranty. Extended 5 and 10 year warranties are available.

For more information on any of our products or services, please visit us on the Web at: http://www.embedia.com

Technical Specifications

Parameter	Specification		
Line Voltage Input	Universal 110-240 VAC at 50-60 Hz		
Motor Outputs	2 Motor Output; 110-240 VAC (Matched to Line Voltage Input); Max. 10A Per Output (Fuse protected); Max. 15A Combined Total		
Low Voltage Inputs	6 Contact Closure Inputs (3 pairs);		
Communication Network (optional)	BACnet MS/TP; Maximum 127 Devices per Segment; Expandable using BACnet/IP Routers such as ControlPoint MS/TP-IP		
Network Wiring (optional)	1 x Twisted Pair + Ground suitable for RS485 Communication; 1200m / 4000ft absolute max bus Length (limiting to 600m / 2000ft recommended)		
Dimensions	Controller Only —170.00mm (6.69") x 82.60	0mm (3.25") x 20.00mm (0.79")	
Enclosure Options	Metal Enclosure; Standard NEMA 1—8" x 8' ABS Plastic Enclosure; UL94-5VA Flame Ra 127mm x 76.2mm)	,	
GROUP-M2-M-B	GROUP-M2-X-B	Mount-ST-EBV2	








Ordering Information

Orderable Part Number	Description
GROUP-M2-M-B	EB2 GROUP—2 motor BACnet MS/TP controller in 8" x 8" x 4" metal enclosure
GROUP-M2-X-B	EB2 GROUP—2 motor BACnet MS/TP controller with no enclosure
MOUNT-ST-EBV2	Snap Track Mounting Kit for EBv2 type controllers (option for GROUP-M2-X-B)

Custom Panels



Embedia offers a range of pre-designed panel layouts to accomodate multiple motor controllers and companion products. Custom design services are also offered. Embedia's manufacturing facility is a certified panel shop and all ordered panels will be certified and ready for on-site installation.





27-112 Freeport Cres. NE Calgary, AB, Canada T3J 0S9 Phone: +1-403-456-6279